

Specification Flush 44 Cubicle (Floor to Ceiling)

Doors and Pilasters:

- High Pressure Laminate PUR bonded onto 44mm MR core
- Rebated Hardwood Edges, sealed 2 coats AC Lacquer

Natural Veneers, Digital Print HPL and Gloss HPL available at additional cost

Divisions:

- High Pressure Laminate PUR bonded onto 36mm MR core
- Matching Laminate edge detail

Standard Dimensions:

Up to 2700mm overall height x 1500mm deep (partitions to be jointed for manual handling)

Ironmongery:

- Continuous 'T' section Pilaster fixing channel
- Royde & Tucker D-Line Stainless Steel rise and fall hinges
- D-Line Eisenware LARGE TURN and Release SSS 14347802300
- Deadbolt 4871.01 with Excelsior Wrap striking plate/keep
- 38mm 'U' section SAA floor channel
- Hat & Coat hook 90mm c/w buffer T500
- Rear Wall 'T' section division fixing channel
- 3mm door/pilaster cushion gasket

Toilet Roll Holders & Accessories available upon request.

Ironmongery Finish: Stainless Steel as Standard.

Colour Selections: Excelsior Preferred Cubicle & Washroom colour selection or natural veneer. **Special Notes**: Outward opening doors complete with back to back Stainless Steel 'D' Handles.

We recommend that outward opening doors open onto an adjacent solid wall to prevent overstrain on hinges.













